

AUAV00102 Dulux Avista Slip Reducing Additive Powder Coarse

Introduction

SKU
FD278014-250G

Product Overview and Image

Fine white granules.



Features and Benefits

- Disperses readily and evenly through sealer
- Slow to settle or float in sealer
- Polymeric in nature, therefore, more compatible physically with sealers e.g. expansion / contraction
- Generally increases abrasion resistance of sealers.
- Compatible with solvent and water based systems.

Uses

To increase the slip resistance of sealers on floors and for use in all Dulux Avista Sealer Ranges.

Typical Properties

Sizes
250g

Typical Property Notes
Appearance: White granules
Density (g/cc) @25 degrees: 0.90
Maximum Particle Size (microns): 840
Flash Point: > 277 degrees C

Application Guide

Application Procedure and Equipment

Mixing

Pour into sealer slowly, while mixing with a hand paddle.

Application

Apply only into final coat of sealer.

To avoid settling stir through every 2 minutes.

Roller Application

Sealer must be roller applied from a roller tray, do not broom apply.

Avoid excess SRA build up on the edges of the roller. This can lead to roller lines in the surface.

To enhance slip resistance, sealer must be applied thinly, at approx 15m² per L

Health and Safety

SDS Number

PAR009636

SDS Link

[View SDS Link](#)

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Precautions and Limitations

- If left in some solvent type sealers for an extended period (> 4 hours), there is a tendency for swelling and sticking together of particles.
- As with most materials it will slowly wear, hence periodic check of slip resistance is advisable.
- Dulls gloss retention.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.